

REVERSIBLE PLATES



Making our mark



REVERSIBLE PLATES

LEBRERO

TECHNICAL

CHARACTERISTICS

	PVR 2190 G	PVR 2115	PVR 2215	PVR 2325	PVR 2600
Centrifugal force	30 kN	24 kN	30 kN	44 kN	60 kN
Vibration frequency	90 Hz	78 Hz	80 Hz	60 Hz	43 Hz
Forward speed depending on ground	1,5 km/h	1,5 km/h	1,5 km/h	1,2 km/h	1,2 km/h
Plate width	390 mm	390 mm	480 mm	610 mm	900 mm
Compacting efficiency depending on ground	562 m ² /h	562 m ² /h	634 m ² /h	696 m ² /h	800 m ² /h
Compacting depth up to	40 cm	35 cm	40 cm	70 / 60 cm	70 cm
Gradeability up to	30%	30%	30%	30%	30%

ENGINE

	Honda 4 tiempos	Hatz diesel	Hatz diesel	Hatz diesel	Farymann Diesel
Model	GX 160	1B-20	E 673	1D41	41A
Power	4 kw (5,5 CV)	3,1 kw (4,3 CV)	3,4 kw (4,6 CV)	5,6 kw (7,7 CV)	10 kw (13,6 CV)
Frequency	3 600 r.p.m.	3 600 r.p.m.	3 100 r.p.m.	3 000 r.p.m.	2 400 r.p.m.
Fuel consumption	1 l/h	1 l/h	1 l/h	1,2 l/h.	1,5 l/h.
Tank capacity	4 l.	3 l.	4 l.	3 l.	5 l.

DIMENSIONS

Total height (Working)	1 170 mm	1 100 mm	1 170 mm	1 200 mm	1 250 mm
Plate length	778 mm	600 mm	778 mm	826 mm	996 mm
Total length with pole (Working)	1 407 mm	1 300 mm	1 430 mm	1 610 mm	1 810 mm
Mass	185 kg	118 kg	212 kg	345 kg	623 mm

SETRA / LCPC CLASSIFICATION

PQ 3	PQ 3	PQ 4	PQ 4	PQ 4
------	------	------	------	------



GENERAL CHARACTERISTICS

- DIESEL OR PETROL ENGINES
- MOVEMENT AND VIBRATION CONTROLS ON HANDLES
- ENGINE PROTECTION ARCH
- SAFETY ENGINE STARTING CRANK
- SINGLE LIFTING POINT
- ABRASIVE RESISTANT BASE PLATE
- EASY TO HANDLE
- GREAT COMPACTING THICKNESS
- EFFICIENCY AND RELIABILITY



Dealer:

OFFICE AND CENTRAL FACTORY

COMOPLESA - LEBRERO, S.A.

Avda. Alcalde Caballero, nº 32 • Pol. Industrial «El Pilar»
50014 Zaragoza (Spain)

E/P.O. Box 402 • Tel (+34) 976 464 300 • Fax (+34) 976 464 301

http://www.lebrero.com • E-mail: info@lebrero.com